



## MOTORCYCLE SERIES

CODE	Voltage, V	CAPACITY (Ah)	CCA @ -18°C	Diemension mm(±2mm)			Terminal	Weight (with acid), kg	Charging current, A
				L	W	H			
YTX5L-BS	12	5	90	113	70	105	A	2,02	0,5
12N5L-BS	12	5	70	119	59	130	B	1,89	0,5
12N6.5L-BS	12	6.5	85	139	66	102	A	2,32	0,65
YTX7L-BS	12	7	85	113	70	130	A	2,43	0,7
YTX7A-BS	12	7	90	150	87	93	A	2,50	0,7
YTX9A-BS	12	9	120	150	87	105	B	3,07	0,9
12N9L-BS	12	9	120	135	75	139	B	3,07	0,9
12N12L-BS	12	12	150	150	85	130	B	3,41	1,2
YTX14-BS	12	14	160	150	87	146	B	4,40	1,4
YTX20L-BS	12	20	200	175	87	156	B	6,00	2
YTX30L-BS	12	30	300	165	127	175	B	8,50	3

## E-BIKE SERIES

CODE	TYPE	Nominal Voltage, V	CAPACITY (Ah)	Diemension mm(±2mm)			Terminal	Weight (with acid), kg
				L	W	H		
6 DZM 14	DEEP CYCLE	12	14	151,5	99,5	97	M5	4,3
6 DZM 24	DEEP CYCLE	12	24	181	76,5	170,5	M5	6,9
6 DZM 24A	DEEP CYCLE	12	24	188	100	130	M5	7
6 DZM 38	DEEP CYCLE	12	38	267	77	170	M5	9,2
6 DZM 60	DEEP CYCLE	12	60	223	121	175	M6	12,8